

## NX-3200/3300

VHF/UHF DIGITAL TRANSCEIVER  
(Featuring universal audio connector)

**NXDN™** **DMR**



**DMR**  
-based  
TRUNKING **T3&S**

**DMR** >>>>  
Auto Slot  
Select >>>>

**FleetSync®** **5-tone** **GPS** **Bluetooth®**

This versatile handheld radio supports both NXDN and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise- and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Additionally, for expansion capability a software license certification system facilitates extensive customization.

### ● PRODUCT HIGHLIGHTS

- **Multi-protocol digital radio:** Designed to operate under an NXDN or DMR digital, and FM analog protocols
- **Mixed Digital & FM Analog Operation** allows gradual migration at your own pace
- **4-Line Basic Frame** (2 lines of icon & key guide) / 14 Characters
- **5-Line Text Message Frame** (3 Lines of Text, icon & key guide)\*
- **7-Color Light Bar Indicator** on the top panel
- **4-way Directional-pad (D-pad)** for intuitive control and operation
- **Built-in GPS Receiver/Antenna** for effective fleet management
- **Built-in Bluetooth** for hands-free operation – Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- **Renowned KENWOOD Audio Quality with Active Noise Reduction (ANR)** that utilizes built-in DSP
- **Software DES and AES** Encryptions for Digital protocols
- **Built-in Motion Sensor** (Man-down, Stationary and Motion Detection)
- **MIL-STD-810 C/D/E/F/G**

\*The number of lines may vary depending on the display language (character set).

### ● GENERAL FEATURES

- **Universal Audio Connector** with 14 contacts to connect with a variety of options, as well as loud audio output and dual mic Active Noise Reduction (ANR) capabilities

- Audio Output Power: 1 Watt
- Intrinsically Safe Option
- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

### ● DIGITAL - NXDN MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

### ● DIGITAL - DMR MODE

- S-Trunking\*
- DMR Tier III Trunking
- DMR Tier II conventional
- DMR Auto Slot Select
- Site Roaming
- 12.5 kHz Two-slot TDMA channels
- Call Interruption
- Dual-slot Direct Mode
- Enhanced Encryption
- Energy Efficient

### ● ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Selective Call, Emergency, Radio Check / Inhibit
- QT / DQT, DTMF, 5-tone
- Built-in Voice Inversion Scrambler



Full Keypad Model

Standard Keypad Model

Basic Model



\* Support for S-Trunking ended.

## OPTIONAL ACCESSORIES


- **KNB-55L/57L/78L**  
Li-ion BATTERY PACK  
(7.4 V/1480 mAh,  
7.4 V/2000 mAh,  
7.4 V/2860 mAh)
- **KNB-56N**  
Ni-MH BATTERY PACK  
(7.2 V/1400 mAh)
- **KNB-79LC**  
Li-ion BATTERY PACK  
(7.4 V/2860 mAh,  
Intrinsically Safe)
- **KBP-5**  
BATTERY CASE (6 AA)



- **KSC-25LS/25S**  
RAPID CHARGER  
(Li-ion Only/Tri-Chem)



- **KSC-256A**  
MULTIPLE CHARGER  
(6-pocket)



- **KRA-22/23**  
VHF/UHF HELICAL  
ANTENNA  
(Low Profile)



- **KRA-26**  
VHF HELICAL ANTENNA  
(Standard Length)



- **KRA-27**  
UHF WHIP ANTENNA  
(Standard Length)



- **KRA-41/42**  
VHF/UHF STUBBY  
ANTENNA



- **KBH-11**  
BELT CLIP (2.5 in)



- **KMC-41D**  
SPEAKER MICROPHONE [IP54/55]\*



- **KMC-54WD**  
SPEAKER MICROPHONE [IP67]\*  
(DSP Active Noise Reduction)

\*To be discontinued

- **KMC-70**  
SPEAKER  
MICROPHONE [IP68]  
(3-button, DSP Active Noise  
Reduction; Green Housing [GR]  
version is also available)



- **KMC-72**  
SPEAKER MICROPHONE [IP67]  
(2-button, Built-in noise canceler)



- **KPG-180AP**  
OTAP MANAGER (PC software)

All accessories and options may not be available in all markets.  
Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

## SPECIFICATIONS

GENERAL		NX-3200	NX-3300
Frequency Range		136-174 MHz	400-520 MHz
Max. Channels per Radio		Up to 1000 channels with option	
Number of Channels		512 (64 for no LCD models)	
Number of Zones		128 (4 for no LCD models)	
Channel Spacing	Analog	12.5 / 20 / 25 kHz	
	Digital	6.25 / 12.5 kHz	
Power Supply		7.5 V DC ±20 %	
Battery Life*1 (Average battery life at 5-5-90)	KNB-55L (1480 mAh)	FDMA Conv. / Trunk. 8.5 / 6.5 h	TDMA Conv. / Trunk. 12.5 / 9.0 h
	KNB-56N (1400 mAh)	7.5 / 6.0 h	11.0 / 8.0 h
	KNB-57L (2000 mAh)	12.0 / 9.5 h	17.5 / 13.0 h
	KNB-78L (2860 mAh)	17.5 / 13.5 h	25.0 / 18.5 h
	KNB-79LC (2860 mAh)*2	15.0 / 11.5 h	21.5 / 16.0 h
Operating Temperature		-30°C to +60°C	
Frequency Stability (-30°C to +60°C; +25°C Ref.)		± 0.5 ppm	
Dimensions*3 (W x H x D) Projections not included	Radio only	56 x 119.6 x 36.4 mm	
	with KNB-55L	56 x 119.6 x 36.4 mm	
	with KNB-56N	56 x 119.6 x 42.7 mm	
	with KNB-57L	56 x 119.6 x 39.0 mm	
	with KNB-78L/79LC	56 x 119.6 x 44.9 mm	
Weight*4 (net)	Radio only	220 g	
	with KNB-55L	315 g	
	with KNB-56N	410 g	
	with KNB-57L	340 g	
	with KNB-78L with KNB-79LC	385 g 395 g	
Applicable Standards	ETSI (EMC)	EN 301 489-1, EN 301 489-3, EN 301 489-5, EN 301 489-17	
	ETSI (Spectrum)	EN 300 086, EN 300 113, EN 300 219, EN 300 328, EN 300 440, EN 301 166	
	ETSI Safety	EN 60215, EN 60950-1, EN62368-1	

RECEIVER		NX-3200	NX-3300
Sensitivity	NXDN 3 % BER (6.25 kHz / 12.5 kHz)	0.20 µV / 0.25 µV	
	NXDN 1 % BER (6.25 kHz / 12.5 kHz)	-4.0 dBµV (0.32 µV) / -1 dBµV (0.45 µV)	
	DMR 12.5 kHz Digital, 5 % BER	-6 dBµV (0.25µV)	
	DMR 12.5 kHz Digital, 1 % BER	-1 dBµV (0.45 µV)	
	Analog, EIA 12 dB SINAD (12.5/20 & 25 kHz)	0.25 µV	
Selectivity	Analog, EN 20 dB SINAD (12.5/20 & 25 kHz)	-1 dBµV (0.45 µV) / -3 dBµV (0.35 µV) / -3 dBµV (0.35 µV)	
	Analog 12.5 kHz	68 dB	
	Analog 20 kHz	74 dB	
Intermodulation	Analog 25 kHz	76 dB	
	Spurious Rejection	65 dB	
Audio Distortion	3 %		
Audio Output (Internal Speaker)	3 % Distortion	500 mW	
	5 % Distortion	1000 mW	
TRANSMITTER		NX-3200	NX-3300
RF Power Output		5 W / 4 W / 1 W	
Spurious Emission		-36 dBm ≤1 GHz, -30 dBm >1 GHz	
FM Hum & Noise	Analog @ 12.5 kHz	40 dB	
	Analog @ 20 kHz	45 dB	
	Analog @ 25 kHz	45 dB	
Audio Distortion	3 %		
Digital Protocol	ETSI TS 102 361-1, -2, -3, -4		
Emission Designator	16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 11K0F3E, 8K50F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K50F2D, 7K60FXE, 7K60FXD, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D		

\*1 Battery Life is measured with factory default setting, GPS/ Bluetooth OFF.

\*2 Typical value under the condition charged with KCS-25S/25LS.

\*3 Dimensions for Full Keypad/Std Keypad Models

\*4 Weight for Full Keypad Model

Specifications are measured according to applicable standards.

Specifications shown are typical and subject to change without notice, due to advancements in technology.

## APPLICABLE MIL-STD & IP\*5

MIL Standards	Methods / Procedures				
	810C	810D	810E	810F	810G
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temp. Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
International Protection Standards					
Dust & Water		IP54, IP55, IP67			

\*5 All interfaces must be fully sealed with appropriate covers or by designated genuine accessories.

- The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by JVCKENWOOD Corporation is under license.
- NXDN™ is a trademark of JVCKENWOOD Corporation and Icom Inc.
- NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.
- FleetSync® is a registered trademark of JVCKENWOOD Corporation.
- All other trademarks are the property of their respective holders.

JVCKENWOOD U.K. Limited

<https://kenwoodcommunications.co.uk/comm/>

KENWOOD Communications  
Global Website



comms.kenwood.com



ISO9001 Registered  
Communications Systems Division  
JVCKENWOOD Corporation

CL874E-E-2R